SaniForce®

Air-Operated Double Diaphragm Pumps

- Maximum flow rates to 150 gpm (567 lpm)
- Tri-clamp connections
- Fluid pressure up to 120 psi (8.4 bar, 0.84 MPa)
- Durable, lube-free non-sticking air valve



3A and High Sanitation Diaphragm Pumps

- Maximum flow rates to 150 gpm (567 lpm)
- Fluid pressure up to 120 psi (8.4 bar, 0.84 MPa)
- Quick knockdown design for easy cleaning and draining
- Durable, lube-free non-sticking air valve
- Interchangeable flapper and ball checks
- Leak detection available

SaniForce Elevator

- Fluid transfer and supply of low to medium viscosity fluids
- Flow rates ranging from 1.5 to 14 gpm (5.7 to 53 lpm)
- Mobile and stationary options available

Bin Evacuation Systems™ (BES)

- Evacuate materials from 300 gallon (1,135 l) containers without adding water
- Inflatable wiper seals for increased efficiency and faster change-out of bins
- Available with two sanitary diaphragm pumps or up to four sanitary piston pumps
- Pneumatic or electronic control options

Piston Pumps

- Fluid transfer and supply of low to medium viscosity fluids
- Flow rates ranging from 1.5 to 14 gpm (5.7 to 53 lpm)
- Double-ball and priming piston designs

Drum Unloaders

- Unload materials from straight-sided or tapered drums
- Inflatable wiper seals for increased efficiency and faster change-out of drums
- Liner guard to prevent bags from entering pump
- Sanitary flange clamps for quick disassembly

A Complete Line of Chemical Transfer Pumps

Graco pumps are a **dependable**, **easy-to-service** solution for CIP applications.

Husky™ 205

- 1/4 in (6.3 mm) connection
- Max flow: 5 gpm (19 lpm)
- Polypropylene, PVDF

Husky 307

- 3/8 in (9.4 mm) connection
- Max flow: 7 gpm (26 lpm)
- Polypropylene

Husky 515

- 1/2 in (12.7 mm) connection
- Max flow: 15 gpm (57 lpm)
- Polypropylene, PVDF

Husky 1050

- 1 in (25.4 mm) connection
- Max flow: 50 gpm (189 lpm)
- Polypropylene, PVDF

Husky 15120

- 1-1/2 in (38.1 mm) connection
- Max flow: 120 gpm (454 lpm)
- Polypropylene, PVDF

Husky 2200

- 2 in (50.8 mm) connection
- Max flow: 200 gpm (757 lpm)
- Polypropylene, PVDF

Hydra-Clean®

- High pressure cleaning and sanitizing
- Air-operated and hydraulic for hazardous or confined areas 10:1, 12:1, 23:1, 30:1 or 45:1 ratio options
- Available in wall, cart or drum mount packages

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Call today for product information or to request a demonstration.

877.84GRACO (1-877-844-7226) or visit us at www.graco.com/sanitary

©2014 Graco Inc. Form No. 345067 Rev. A 12/14 Printed in the U.S.A.
All other brand names or marks are used for identification purposes and are trademarks of their respective owners.

GRACO